



S 26-32-36-40-45-50-55

CESOIA IDRAULICA
CONCRETE STEEL CUTTING MACHINE
CISAILLE HYDRAULIQUE POUR FER À BETON
CIZAILLAS HIDRAULICA

| Dati Tecnici - Technical data - Donnees Techniques - Caracteristicas | | | | | |
|---|---|---|--|--|---------------------------------|
| Mod. | Motore Motor Moteur Potencia motor | Lunghezza Lenght Longueur Longitud | Larghezza Width Largeur Anchura | Altezza Height Hauteur Altura | Peso Weight Poids Peso |
| S 55 | Hp 7,5 | mm 890 | mm 510 | mm 850 | Kg 500 |
| S 50 | Hp 7,5 | mm 1.330 | mm 680 | mm 870 | Kg 420 |
| S 45 | Hp 5 | mm 1.330 | mm 680 | mm 870 | Kg 380 |
| S 40 | Hp 4 | mm 1.330 | mm 680 | mm 870 | Kg 370 |
| S 36 | Hp 3 | mm 1.150 | mm 600 | mm 730 | Kg 250 |
| S 32 | Hp 3 | mm 1.050 | mm 530 | mm 910 | Kg 215 |
| S 26 | Hp 3 | mm 890 | mm 510 | mm 850 | Kg 150 |

| Prestazioni - Performance - Caracteristiques - Caracteristicas | | | | | | | | | |
|---|-----------------------|----|-------|-----------------------|----|-------|-----------------------|----|-------|
| Mod. | 45 Kg/mm ² | | | 65 Kg/mm ² | | | 85 Kg/mm ² | | |
| | ∅ | ∕ | ▭ | ∅ | ∕ | ▭ | ∅ | ∕ | ▭ |
| S 55 | 55 | 50 | 80x25 | 50 | 40 | 70x20 | 45 | 35 | 70x15 |
| S 50 | 50 | 40 | 60x20 | 42 | 34 | 60x15 | 40 | 30 | 50x20 |
| S 45 | 45 | 36 | 40x20 | 34 | 30 | 35x20 | 32 | 24 | 30x15 |
| S 40 | 40 | 32 | 40x20 | 32 | 26 | 30x20 | 30 | 22 | 25x20 |
| S 36 | 36 | 28 | 35x15 | 30 | 24 | 30x15 | 26 | 22 | 25x15 |
| S 32 | 32 | 26 | 30x15 | 26 | 20 | 25x15 | 24 | 18 | 20x15 |
| S 26 | 26 | 26 | 30x15 | 22 | 20 | 25x15 | 20 | 18 | 20x15 |

SILLA Macchine Edili e Stradali S.r.l.
 53036 POGGIBONSI (SI) ITALY - Via San Gimignano, 96
 Tel. +39.0577.938.051 - Fax +39.0577.981.609
 e-mail: info@sillaitaly.com - www.sillaitaly.com